



HUMIDUR® Single Coat System

About ACOTEC and HUMIDUR

- > ACOTEC's = Anti COrrosion TEChnology
- Headquarters based in Belgium
- ➤ HUMIDUR® = HUMIdity + DURability

MOBILIE COFFERDAM DZI for Submerge Application

- > Safe and dry access to submerged areas
- > No divers required
- > Sheet piles, tubular piles, capping beams, ...
- > Customisable for each application





For enquiries, please contact us at

Phone : +603 2711 1011



5 Humidur systems covers most structures compared to 100

√ Successful in all types of water environment

- Proven system in salt brackish fresh water
- Officially approved for potable drinking water structures

✓ Ideal for structures in water

- Works in fully submerged zone, tidal / splash zone and atmospheric zone
- Perfect for pipelines, offshore and marine structures, ballast tanks

✓ Increased Flow velocity

- Smooth surface
- Perfect in moving water
 increase flow velocity, capacity

✓ Cures under water

- Immediate use of structure
- Minimum downtime
- Unique efficiency in coating of submerged and splash zones!

√ Single-layer system


- 1 layer built up to the requested DFT
- No primers required
- Reduced production and application costs substantially

User friendly; min surface preparation

- > 30-year claim-free system and satisfied customers worldwide
- Ideal solution for Sweating Lines and CUI
- Surface tolerant: even under minimal surface preparation conditions the coating withstands extreme conditions (adhesion values reach up to 25 MPa)

Proven system in petrochemical environments for decades

Products: Crude oil, Kerosene, Jet Fuel A1, Gasoline, Biodiesel, Palm oil, Sulphuric acid (20%), Hydrochloric acid (32%), Nitric Acid (20%), Waste water







Clients: PETRONAS, MISC, Enquest, Woodside, Brunei Shell, Brunei LNG, Shell, ExxonMobil, Statoil, BP, Marathon, Talisman Energy, Total Oil & Gas, Texaco, Sinopec, Lynergy, Conoco Phillips -Onshore/Offshore, Chevron Offshore, BG Trinidad Offshore, Technip Offshore, BG India Offshore, Reliance Oil Refinery (Largest refinery in the world) India, Transocean Drilling Offshore, Bibby Offshore, Subsea7, Maersk Oil & Gas, Fairfield Energy Offshore, etc.

For enquiries, please contact us at

Phone : +603 2711 1011



Key Benefits

Cost Effective

- Single Coat
- Minimal surface preparation and shutdown
- No Primer and Top Coat required
- Allows for NDT inspection at 400µm DFT
- 1/3 losses compared to 3 layer coating system
- ➤ Up to 30 Year Warranty



- Up to 40% productivity increase over 3-layer system
- ➤ No revisit for 2nd and 3rd coat application 1 day application time vs. min 3 days for 3-layer system
- No intermediate curing times for multiple layers
- Cures Underwater

> Increased Window of Application

- Can be applied :
 - In high humidity conditions i.e. as high as 95% Humidity
 - Within a temperature Range -35°C to 150°C
 - To pH levels 0 < pH < 14
 - To salt levels < 65 mg/m2







For enquiries, please contact us at

Phone : +603 2711 1011



> Enhanced HSE Management

- ➤ It is environmentally friendly (no VOC's, no coal tar, no heavy metals, no isocyanates)
- Eliminates need for multiple solvents/chemical
- No risk of pollution; solvent free no heavy metals, coal tar or isocyanates
- No leaching when curing under water
- > No HSE risk 100% VOC free
- Minimum risk of explosion due to higher flash point (>100°C)



SUMMARY

- Provides the Asset Owners with the best in class solution to meet the challenge of keeping costs down and increasing productivity
- Ideal for fabric maintenance activities both offshore and onshore
- Accreditations include Norsok M-501, IMO, TAMAP, SGS etc
- Received Shell Global TRT (Technology Replication Thrust) recognition in one layer anti-corrosion coating and is currently being replicated worldwide. Regionally Malaysia, Singapore, Brunei and Philippines have commenced Humidur application
- Saudi-Aramco approval obtained in February 2017. The tests conducted were far more severe than the Norsok test program



For enquiries, please contact us at

Phone : +603 2711 1011